



Data sheet

IM 253CAN, CANopen slave (253-1CA30)

Technical data

Order no.	253-1CA30
Type	IM 253CAN, CANopen slave
General information	
Note	-
Features	CANopen slave 10 Rx and 10 Tx PDO 2 SDOs PDO linking PDO mapping
Technical data power supply	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	
Current consumption (no-load operation)	50 mA
Current consumption (rated value)	300 mA
Inrush current	60 A
I^2t	0.4 A ² s
Max. current drain at backplane bus	0.8 A
Max. current drain load supply	-
Power loss	1.5 W
Status information, alarms, diagnostics	
Status display	yes
Interrupts	yes, parameterizable
Process alarm	no
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes, parameterizable
Diagnostics information read-out	possible
Supply voltage display	yes
Service Indicator	-
Group error display	yes
Channel error display	none
Hardware configuration	
Racks, max.	1
Modules per rack, max.	8
Number of digital modules, max.	8
Number of analog modules, max.	8
Communication	
Fieldbus	CANopen
Type of interface	CAN
Connector	Sub-D, 9-pin, male
Topology	Linear bus with bus termination at both ends

Electrically isolated	
Number of participants, max.	127
Node addresses	1 - 99
Transmission speed, min.	10 kbit/s
Transmission speed, max.	1 Mbit/s
Address range inputs, max.	80 Byte
Address range outputs, max.	80 Byte
Number of TxPDOs, max.	10
Number of RxPDOs, max.	10

Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Weight	90 g

Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL508 certification	yes
---------------------	-----