

## Data sheet

### IM 261, Row interface (261-1CA00)

#### Technical data

<b>Order no.</b>	<b>261-1CA00</b>
Type	IM 261, Row interface
<b>General information</b>	
Note	-
Features	Only be used in conjunction with the PC 288 or a CPU
<b>Technical data power supply</b>	
Power supply (rated value)	-
Power supply (permitted range)	-
Reverse polarity protection	-
Current consumption (no-load operation)	-
Current consumption (rated value)	-
Inrush current	-
Max. current drain at backplane bus	1.5 A
Max. current drain load supply	-
Power loss	1 W
<b>Status information, alarms, diagnostics</b>	
Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	yes
Group error display	none
Channel error display	none
<b>Hardware configuration</b>	
Racks, max.	1
Modules per rack, max.	16
Number of digital modules, max.	16
Number of analog modules, max.	16
<b>Housing</b>	
Material	PPE
Mounting	Profile rail 35 mm
<b>Mechanical data</b>	
Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Weight	90 g
<b>Environmental conditions</b>	
Operating temperature	0 °C to 60 °C

Storage temperature -25 °C to 70 °C

---

### Certifications

---

UL508 certification yes

---